# NR.2 TYPE SPECIFICATION/CONTRACT BID SUBMISSION FORM

**Company Name:** 

AD Nr: 2021/ESA-244A

ITEM NR	TEM	TRANSPORT WORK	THE LOADING	THE	GROSS QUANTITY OF	UNIT PRICE OF		Bandırma		
	NR		PORT	DISCHARGING PORT	WORK (TONs) (A)	BID (EUR/TON) * (B)	OF BID (EUR) (A*B)	LAYCAN		
	1	MISC. BORON PRODUCTS	Bandırma	KOPER	6118.3 (+/- % 5 ETİ option)	0	0	03.12.2021-08.12.2021		

Total: 6118.3 Total: 0

#### NOTES:

1. This form is sign by authorized personal.

2. The bidders who are not in our repertoire declare to accept terms and condition of Nr.2 type specification/contract [that is find on website wwww.etimaden.gov.tr] on the Bid Submission Form and the requested documents and information that seen in same place by ETİ would be deemed to have committed in order to recorded to repertoire.

3. The bids is given via the Bid Submission Form and this Form and its attachment that included details of shipping & transport are signed and cached.

4.The nomination of ship and the Bandirma ETA must be given within the bid submission form and the Bandirma ETA must be suitable to Bandirma LAYCAN.

If the ship nomination & the Bandirma ETA are not given by bidders or the Bandirma ETA is not suitable to Bandirma Laycan, the bids will be disqualified.

5.The bidder accepts all terms of Type 2 Specification/contract and the details of shipping and transport.

6.In case a bid is given by the real and legal persons which is notified as affiliation and/or connected with terrorist organization by security and intelligent authorities, their bids are invalid and if contract was signed, it will be canceled and both of these situations firms will be banned. Bidder/Contractors do not have any right in these cases.

**VESSEL IMO:** 

**LAST 4 CARGOES:** 

**LOADING PORT ETA:** 

**ENC: DETAILS OF SHIPPING & TRANSPORT** 

ADDITIONAL INF. FOR YOUR BID

--

#### **DETAILS OF SHIPPING AND TRANSPORT**

- 1. The bidder will offer all of the work (items).
- 2. All of shipment shall be carried out from the loading ports/berths/terminals to unloading ports/berths/terminals by one ship and in the hold(s) of the ship and without a partial cargo.
- 3. The unloading will be made to buyer's berth is notified Buyer's agency.
- 4. All or some cargo could be directly transshipped into barge(s) and/or coaster(s).
- 5. The bill of lading(s) shall have got the phrase as 'Clean on Board'. The B/L(s) shall be delivered to ETİ without delay.
- 6. The holds will be reinforced with hatch cover marine tape (in min. 150 mm widths and at min. 5 mm thickness) or with foam by the Contractor in order to minimize water leakage.

## BASIS OF TRANSPORT: FIOST lashing / securing / dunnage

Bandırma PORT LAYCAN: 03.12.2021-08.12.2021

Contractor shall be obliged to make available at Bandırma port, the ship that is suitable to the loading port/berth/terminal and to the discharge port/berth/terminal between 03.12.2021-08.12.2021 following his reception of the transportation instructions from the ETİ

ETA NOTICE: The ship shall report her estimated time of arrival (ETA) to loading and unloading ports at 7, 5, 3, 2 and 1 days intervals to ETİ and sales@etiproducts.com.

QUANTITY OF THE WORK: Total: 6118.3 (+/- 5% option)
THE DEADLINE FOR BIDDING: 25.11.2021 13:30:00
BUILT DATE OF VESSEL MUST BE MAX 25 YEARS

DETAILS OF PRODUCTS

2600 tons BIG -75 mic Ground Colemanite(P2060597) in 1000 kg big bags without bottom valves,

2600 tons BIG -45 mic Ground Colemanite(P2060598) in 2000 kg big bags without bottom valves,

400 tons BAN NS Boric Acid(P2157599) in 1000 kg big bags with bottom valves,

300 tons EME LS Boric Acid(P2057601) in 1000 kg big bags with bottom valves,

200 tons KIR Etibor-48(P2158602) in 1000 kg big bags with bottom valves,

Total NET 6100 tons

Total GROSS 6118.300 tons
IMPORTANT NOTES:
· Big bags must be stored maximum 6 tiers.
The palletized products should be loaded in 3 tiers.
· All products will be loaded in one of Çelebi Terminal's piers is determined by the Contractor's agency.
· Product types and tonnages could be changed by ETİ within 5% option.
· The products are harmless, non-dangerous and non imo classed.
The holds of vessel must be reinforced with hatch cover marine tape (in min. 150 mm widths and at min. 5 mm thickness) or with foam by the Contractor in order to
minimize water leakage
DETAILS OF SHIP
· The hatches of holds must be MacGregor type or hydrolic endrolling type automatic hatches.
The vessel(s) has/have not carried any cargo of waste, derived products of petrol, petroleum and coal products, scrap, derived products of coal, refused-

The vessel(s) has/have not carried any cargo of waste, derived products of petrol, petroleum and coal products, scrap, derived products of coal, refused-derived fuel (RFD)

or solid recovered fuel and specified recovered fuel (SRF) during the last one year in addition to 2 Nr. Type Specification.

The holds, hatch covers and interior and exterior walls of the holds of the ship(s) must be free of rust and dirt. Hatch covers must be isolated to water

leakeges.

Shipowner(s) and ship(s) must be a member of IACS or Turk Loydu.

Vessel should not been under detention within a year.

The ship should be suitable for the characteristic and climatic condition of the loading and unloading ports and the ship should be have proper depth holds in order to use crane and

its grabber.

The Holds of Ship: The holds of the ship(s) should be double-skinned and box-shaped type and bulk head type. The holds shall have steel floors. The holds should be at the same size with the

hatches, in "OPEN HATCH" form, with an automatic opening and closing feature.

#### **DETAILS OF LOADING PORT**

## Bandırma Eti Maden Berth (pier):

Length: approximately 180 meter

Width: approximately 80 meter

Berth draft: SSW approximately 8,00 meter

1gsb (good, safe berth) & aa (always afloat)

Loading rate: approximately 5400 tons per WWD for bulk

## Çelebi Terminal:

### Berth Length & drafts

Berth Nr.	Length approximately (meter)	Approximately DRAFT SSW (Summer Salt Water) (METER)
2-3	284	9
4-5	324	10
6	130	10
7-8	380	11 for 250 meter section of berth 10 for 130 meter section of berth
9	204	10
11	190	10

Width: approximately 80 meter

1gsb (good, safe berth) & aa (always afloat)

Loading rate: approximately 1500 tons per WWD for Big-Bag & 750 tons per WWD for pallets.

## **DETAILS OF DISCHARGING PORT**

1	1 SAFE				BERTH,								<b>KOPER</b>	
Discharging	rate:	weather	working	day	SSHEX	Working	hours	of	port:	Mon-Fri	06:00		-	20:00
A.		For		bulk:		1750		tons		/				WWD,
B.	For	big	bags	(1000kg	and	2000kg)	:	1000	big	bags		/		WWD,
Discharging		rates	for		ılk	and	ba	ıgs	are	n	ot		C	umulative.
Unloading berth will be notified by the agency of discharging port.														

The information as special characteristics, administrative and technical conditions, icing and other climatic conditions of the discharging port should be observed while the most suitable ship is

provided by the Contractor. That's why, all costs and expenses borne by the Contractor in case of the ship stay at sea and/or ports due to climatic condition and icing and/or not berth to port/terminal/piers due to same and other reasons.

### THE LOADING AGENCY

The loading agency of Contractor must be localized in Bandırma and it must being worked as shipping agency under permit and license of TC Maritime Undersecretary and should have managed the loading operation of bulk/bags/palletized products.

### THE DISCHARGING PORT AGENCY OF BUYER

### **KOPER**

Adria Cargo Koper doo Pristaniska 8, 6000 Koper, Slovenia

Tel: 00386 5 66 34 131 Fax: 00386 5 66 34 149 Gsm:00 386 31 372 883 e-mail: agent@ackp.si